



CU1-001
(UART)



MC1-001
(IP67, CAN Bus, RS-232)



MU1-001
(IP67, UART)

The WASP™-200 series of rangefinders are LiDAR sensors designed to measure ranges of 200 m off of non-cooperative targets with remarkable accuracy and precision in an ultra-tiny package with FDA Class 1 laser certification. The WASP™ Laser Rangefinder provides robust measurements off of low-reflectivity targets. It uses single shot time of flight (ToF) ranging which allows it to work from fast moving vehicles on fast moving targets. It is designed with a host of advanced features making the WASP™ series of rangefinders well-suited for a variety of applications. The WASP™ Laser Rangefinder can identify targets beyond 300 meters away at a rate of up to 56 ranges per second with custom options to 10 KHz, and with accuracy better than 10 cm at 200 m and performance over water.

Highlights

- High repetition rate for fast single-shot ranging for fast scanning and moving platforms
- Programmable burst mode averaging
- Class 1 Laser Product
- IP 67 option
- Optional fields of view available for proximity detection applications
- ArduPilot supported (Plane, Copter, and Rover)
- Connector options including pigtails
- Durable molded ABS plastic housing
- Integrated back or front mounting

Software Features

- Programmable burst mode and moving averaging for enhanced precision
- Programmable burst mode averaging
- Background solar noise detection and compensation
- Programmable sensitivity and range offsets

Applications

- Robotics and Drones
- Scanned LiDAR
- Sense and Avoid
- Height Above Ground (HAG) flight
- Industrial Automation
- Height & Distance Measurements
- Maritime Operations
- Precise Proximity Detection

SYSTEM FEATURES

WASP™ 200-LRF



CU1-001



MU1-001



MC1-001

Specifications

Laser Eye Safety	Class 1 Laser Product		
Range Performance	0.15 m to 175 m 18% reflectivity		
Range Performance *Full Sun Conditions	0.1 m to 300 m 80% reflectivity		
Maximum Range	315 m		
Accuracy	< 10 cm		
Spectral Band	905 nm		
Resolution	1 cm		
Update Rate	Single shot to 56 Hz Class 1 and Class 3R	Single shot to 50 Hz	
Wavelength	905 nm		
Beam Divergence	8 mrad x 1 mrad		
Optical Aperture	18 mm		
Input Voltage	3.5 V to 16 V		3 V to 16 V
Operating Current	< 75 mA @ 5 V Operating Voltage		< 75 mA @ 10 V Operating Voltage
Inrush Current	< 100 mA @ 5 V Operating Voltage		< 100 mA @ 10 V Operating Voltage
Connector	8 pin Hirose Connector or Pigtail	ODU IP67	
Communication Interface	UART		CAN Bus, RS-232
Dimensions (L x W x H)	44 x 20 x 42 mm ³	44 x 34.8 x 42 mm ³	
Weight	26 grams	46 grams	46 grams
Operating Temperature	-40 to + 60 °C		
	-40 to 140 °F		



See More



Please scan QR code for more information

Equipment described herein is subject to US export regulations under the EAR as an EAR99 product. Specifications are subject to change without notice. © 2023 Attollo Engineering LLC. All rights reserved. XM000013 R.2023.04.18